
A3 black & white MFP

MP 4054SP MP 5054SP MP 6054SP Series









Highly reliable A3 black & white MFPs

Your organisation is unique. Just like the way you conduct business. So why handle document management in the same way as everybody else does? Ricoh's A3 black & white MFPs are designed for busy mid- to large-sized offices. These MFPs help you print, copy and share a wide range of documents. Use them as your information portal and connect to cloud services and applications directly from the operation panel. Monitor usage, energy consumption, operating costs and more with powerful administration tools. Add this compact device to your Managed Document Service (MDS) programme to reduce costs across your company via advanced document handling. Available in a wide range of configurations, these models match your requirements and enhance your output from creation to finish.

- · Time-saving: rapid recovery from sleep mode and a fast first print speed
- Highly productive: print at up to 40/50/60 pages per minute
- Ease of use: choice of two operating panels (9-inch/10.1-inch)
- Cost-saving: low energy consumption
- Flexible: wide range of models to meet all your needs



So smart. So intuitive. So productive

Easy to use

The MP 4054SP/5054SP/6054SP Series is very simple to use. Select a conventional large 9-inch display (MP 4054(A)SP/MP 5054(A)SP/MP 6054SP) or try out the latest Ricoh 10.1-inch smart operation panel (MP 4054AZSP/MP 5054AZSP/MP 6054ZSP). Touch and swipe, like with any smart device, to perform complex operations rapidly and effortlessly. These models also feature external USB keyboard support, which further improves usability.



Instant action

Ricoh's MP 4054SP/5054SP/6054SP Series wakes up from Energy Saver mode virtually instantly. Turn away briefly and you'll miss the first print at a quick 2.9 seconds. Their high paper capacity of maximum 4,700 sheets and thick paper support of up to 300 gm² are complemented by an Automatic Reversing Document Feeder (MP 4054SP/MP 5054SP) or a Single Pass Duplex Feeder (MP 4054A(Z)SP/MP 5054A(Z)SP/MP 6054(Z)SP) for fast double-sided printing.

Top-quality documents

A large variety of finishing options is available. Add one of the two booklet finishers to easily create flat fold booklets. This saves you time that would otherwise be spent on manually folding documents. You can also opt for the 1,000- or 3,000-sheet finisher for a professional touch.



Enhance your green credentials

Low Total Electricity Consumption (TEC) values, energy-saving sleep mode and new Energy Star v2.0 compliance reduce your environmental impact and your energy costs. Automatic and fast double-sided printing is standard to save time, paper and cost.

MP 4054SP/MP 5054SP/MP 6054SP Series

MAIN SPECIFICATIONS

GENERAL

Warm-up time: 14 seconds First output speed: 4/2 9/2 9 seconds Continuous output speed: 40/50/60 pages per minute

2 GB Memory: HDD: 320 GB

With ARDF: 587 x 680 x 913 mm Dimensions (W x D x H): With SPDF: 587 x 680 x 963 mm

With ARDF: 68.5 kg Weight: With SPDF: 74 kg 220 - 240 V, 50/60 Hz Power source:

COPIER

Copying process: Twin laser beam scanning and electro-

photographic printing Multiple copying: Up to 999 copies Resolution: 600 dpi

From 25% to 400% in 1% steps 700m

PRINTER

Printer language Standard: PCL5e, PCL6(XL), PDF

direct print

Option: XPS. Adobe® PostScript®

3™, IPDS

Print resolution: Maximum (1,200 x 1,200 dpi)

Interface: Standard: USB2.0 Type A, USB2.0 Type B, SD slot, Ethernet 10 base-

T/100 base-TX, Ethernet 1000 Base-T Option: Bi-directional IEEE 1284. Wireless LAN (IEEE 802.11a/b/g/n) Bluetooth, Additional NIC (2nd port) TCP/IP (IP v4, IP v6), IPX/SPX

Windows® environments: Windows® XP, Windows® Vista, Windows® 8, Windows® 8.1, Windows® Server 2003, Windows® Server 2012. Windows® Server

Mac OS environments: UNIX environments:

Network protocol:

Macintosh OS X Native v10.6 or later UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux, IBM®

AIX

Novell® Netware® environments v6.5

SAP® R/3® environments: SAP® R/3®

NDPS Gateway, AS/400® using Other supported environments: OS/400 Host Print Transform, IBM

iSeries

SCANNER

ARDF: Max. 80 originals per minute Scanning speed

SPDF: Max. 110(simplex)/180(duplex) originals per minute

Standard: 100 - 600 dpi Resolution: A3, A4, A5, B4, B5, B6 Original size Bundled drivers: Network TWAIN

E-mail, Folder, USB, SD card Scan to:

FAX

Circuit: PSTN. PBX Compatibility: ITU-T (CCITT) G3

Resolution: 8 x 3.85 line/mm, 200 x 100 dpi

8 x 7.7 line/mm, 200 x 200 dpi Option: 8 x 15.4 line/mm, 400 x 400 dpi16 x 15.4 line/mm, 400 x 400 dpi

Transmission speed: G3: 2 second(s) Maximum: 33.6 Kbps Modem speed: Memory capacity: Standard: 4 MB Maximum: 60 MB

PAPER HANDLING

A3, A4, A5, A6, B4, B5, B6 Recommended paper size: Paper input capacity: Standard: 1,200 sheets

Maximum: 4,700 sheets Paper output capacity: Standard: 500 sheets Maximum: 3,625 sheets

Standard paper tray(s): 60 - 300 g/m² Paper weight:

Bypass tray: 52 - 300 g/m² Duplex: 52 - 256 g/m²

ECOLOGY

Maximum: 1.78 kW Power consumption:

Ready mode: 81.4 W Sleep mode: 0.51 W

TEC (Typical Electricity Consumption):

1.607/2.253/2.719 Wh

SOFTWARE

Standard: Web Image Monitor

GlobalScan NX, Streamline NX, Card Optional Authentication Package, Enhanced Locked Print, Unicode Font Package

for SAP

OPTIONS

1 x 550-sheet paper tray, 2 x 550-sheet paper tray, 2,000-sheet large capacity tray, 1,500-sheet side large capacity tray, Bridge unit, 1,000-sheet finisher, 3,000-sheet finisher, Internal finisher, 1,000-sheet booklet finisher, 2,000-sheet booklet finisher, Punch kits, Internal shift tray, One-bin tray, Side tray, Caster table, Bi-directional IEEE 1284, USB Device Server, Bluetooth, Netware, PostScript3, IPDS unit, Browser unit, Counter interface, File format converter, Key counter bracket, Card reader bracket, Copy Data Security Unit, Fax Connection Unit, 2nd Super G3 port, Fax memory, Fax option, Wireless LAN (IEEE 802.11a/g/n), OCR Unit, Smart Card Reader Built-in Unit, XPS direct print, Enhanced security HDD, Kevboard bracket

CONSUMABLES

Toner target yield (A4/LT, 6% Black: 37,000 prints coverage):

The internal finisher is not an option for the 60 ppm models. For availability of models, options and software, please consult your local Ricoh supplier

























ISO9001 certified ISO14001 certified. ISO27001 certified

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2015 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.



www.ricoh-europe.com

Ricoh UK Ltd.

1 Plane Tree Crescent Feltham Middlesex TW13 7HG

Tel.: +44 (0) 20 8261 4000 Fax: +44 (0) 20 8261 4288 www.ricoh.co.uk